

A4 STORM REGENERATIVE AIR SWEEPER 3.6m³







REGENERATIVE AIR SWEEPER 3.6m³

The Schwarze® A4 Storm™ is a chassis mounted, regenerative air street sweeper and a real heavyduty workhorse that will provide a high-quality option with the lowest cost of ownership. It also includes Schwarze WhisperWheelSM fan system, which runs over 70% quieter and up to 20% less fuel consumption.

Airspeed of 14,000cfm and sweep path of 3,048mm makes this package the compact performance leader. High tipping at 1,956mm and overall height of 2,505mm puts the A4 in a class of its own. As the regenerative air system raises much less dust than sweepers fitted with main brooms, less water is required for dust control.



^{*}Typical measurements shown. Exact dimensions depending on options and truck manufacturer



Variant	Schwarze A Regenerativ	
Chassis	ISUZU NQR AMT, Dual C	
Debris hopper	Capacity 3.6 Usable capa	
Material	3.4mm 3CR	12 SS plate
Aux. engine	Cummins Q Turbo Diese Tier IVF	
Sweeping path		
Dual suction nozzles, dual side brooms and 3,050mm transfer brooms		3,050mm
Suction nozzle, transfer brooms and one side broom 2,775mm		
Suction nozzle only		2,032mm
Instrumentation		
Auxiliary engine	Cummins fla panel displa	
Fan system		
Туре	Whisper Wheel (closed face radial fan)	
Performance	20,388 m ³ / (12,000cfm	
Construction	Hardox stee	el
Drive	Direct via si	ngle belt
High tipping		
Hopper tipping height		1.8m
Hopper tipping angle		90 degrees
Tiopper tipping		, 5 4.50.555

Dust supression	Dust supression system		
Water pump type	Diaphragm Run-Dry		
Water tank size	750 litres		
Tank material	Polyethylene		
Controls	Electric in cabin		
Nozzles	7 on front spray bar 2 on each broom 2 inside suction nozzles 4 on pickup head 4 on hopper spray 2 on hopper intake		
Pickup head			
Туре	Dual chambered full width blast orifice		
Operating direction	Forward		
Suspension	Adjustable spring balanced		
Nozzle width	2030mm		
Suction hose diameter 300mm			
Hose construction	Wire-reinforced, 9.5mm, thick molded rubber		
Head area	1.3m ²		
Leaf flap	Electric open and close		
Controls	Hydraulic raise and lower		
Construction	Abrasion-resistant steel with corded rubber seal flaps		

Brooms		
Туре	Vertical steel digger	
Location	Right and left; forward of pickup head	
Diameter	990mm	
Drive	Hydraulic	
Suspension	Torque sensing spring	
Wear adjustment	Automatic	
Pressure	Manual	
Speed	Variable; non-reversing	
Segments	4 per side	
Tilt angle adjustment	Variable, in-cab control	
Electrical system		
Sweeper aux. en	gine 12V	
Aux. engine alternator 55 amp		
Hydraulics system		
Drive	Gear pump	
Reservoir	61 litres	
Controls	Electro-hydraulic	
Aux hydraulics system		
Gear type	Driven by 12V electric motor	
Function	Raise/lower hopper and pickup head; open/ close hopper door; extend/retract brooms	
Paint		
Polyurethane 3 coat system, white		

The Schwarze A4 Storm[™] is the only compact sweeper with full size performance in the market High tipping with over 3m sweep path ensures productivity unmatched in a small package.

01

CURB SWEEPING

The preferred choice of many Councils and Contractors for highest productivity and reliability. The highest performance 'Regen' ensures higher quality clean with an increased speed.

02

INDUSTRIAL / CIVIL SWEEPING

Highest performance vacuum with larger gutter brooms, 12" intake hoses, bigger, stronger pick-up heads, and it serves as the best contractor sweeper.

03

PIT CLEANING

17,000cfm gives a significant advantage to crossover into efficient pit cleaning activity. 8" rear mounted hose and washdown handgun makes lightwork of solid material with pit cleaning and catch basins.

